



### Applications

- Roads
- Play areas
- Site works
- Drives
- Paths
- Patios

## mastaTEX® Non-Woven Handy Rolls

Needlepunched Nonwoven Polyester Geotextile

Manufactured to ISO9001 accredited quality standard.

mastaTEX® Handy Rolls Specifications			
Physical Properties	Standard	Unit	Typical Value
Nominal Thickness	AS 3760.1 ASTM D5199	mm	1.0
Typical UV Resistance	AS 3706.11 ASTM D4355	% retained	>50
Mechanical Properties			
Wide Width Tensile Strength (MD/CD)	AS 3706.2 ASTM D4595	kN/m	6.0
CBR Puncture Resistance	AS 3706.4 ISO 12236	N	1200
Trapezoidal Tear Strength (MD/CD)	AS 3706.3 ASTM D4533	N	200
Grab Tensile Strength (MD/CD)	AS 2001.2.3.2 ASTM D4632	N	500
G Rating	Austrroads VicRoads RC 381.01	Robustness Classification	>900
Hydraulic Properties			
Pore Size Distribution	AS 3706.7 ASTM D4751	Microns	<200
Flow Rate (10cm Constant Head)	AS 3706.9 ISO 11058	L/m <sup>2</sup> /sec	>250
Dimensions			
Size	-	m	0.6m x 50m 1m x 50m 2m x 50m 2m x 100m 4m x 100m

All information and guidelines in this material is given in good faith but without warranty, expressed or implied with respect to the quality or fitness of the product referred to herein for any particular purpose. Values are mean derived from testing over period of time and are correct to the best of our knowledge at the time of publication. The above properties do not represent results from any one particular test batch. These values are subject to change without notice. Unauthorised reproduction or distribution is prohibited.