



# Land Pride & Kubota BX Tractor Series, Performance Matched Implements, Attachments & Loader Attachments

## Performance Matched BX Series Implements

IMPLEMENT TYPE	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	BX1880	BX2380	BX2680	BX23S
<b>Aerators</b>	CA0540**	Drawbar Pull-Type	88 lbs	36"	✓	✓	✓	✓
	CA0548**		106 lbs	44"	✓	✓	✓	✓
	CA0556**		117 lbs	52"	✓	✓	✓	✓
	CA1548**	3-Point Hitch Cat 1	156 lbs	41"	✓	✓	✓	✓
	CA1556**		170 lbs	50"	✓	✓	✓	✓
	CA1564**		184 lbs	58"	✓	✓	✓	✓
	CA1572**		208 lbs	66"	X	✓	✓	✓
<b>Arena Grader</b>	AG1560	3-Point Hitch Cat 1	514 lbs	60"	✓	✓	✓	✓
<b>Box Blades</b>	BB1248	3-Point Hitch Cat 1	316 lbs	48"	✓	✓	✓	✓
	BB1254		325 lbs	54"	✓	✓	✓	✓
	BB1260		346 lbs	60"	✓	✓	✓	✓
	BB1266		370 lbs	66"	X	✓	✓	✓
<b>Disk Harrows</b>	DH1048	3-Point Hitch Cat 1	420 lbs	48"	✓	✓	✓	✓
	DH1060		549 lbs	60"	X	✓	✓	✓
<b>Drag Harrows</b>	DRG04	Drawbar Pull-Type	89 lbs	48"	✓	✓	✓	✓
	DRG06		138 lbs	72"	✓	✓	✓	✓
	DRG08		185 lbs	96"	✓	✓	✓	✓
<b>Field Cultivator</b>	FC10	3-Point Hitch Cat 1	135 lbs	57"	✓	✓	✓	✓
<b>Food Plot Seeder</b>	FPS48**	Drawbar Pull-Type	370 lbs	54"	✓	✓	✓	✓
<b>Grading Scrapers</b>	GS0548	3-Point Hitch Cat 1	310 lbs	48"	✓	✓	✓	✓
	GS0560		350 lbs	60"	✓	✓	✓	✓
<b>Grooming Mowers</b>	FDR1648	3-Point Hitch Cat 1	486 lbs	48"	✓	✓	✓	✓
	FDR1660		577 lbs	60"	X	✓	✓	✓

✓ - Available X - Unavailable



<b>Landscape Rakes</b>	LR0548	3-Point Hitch Cat 1	98 lbs	48"	✓	✓	✓	✓
	LR0560		113 lbs	60"	✓	✓	✓	✓
	LR1660		241 lbs	48"	X	✓	✓	✓
	LR1672		270 lbs	60"	X	✓	✓	✓
<b>Post Hole Digger</b>	PH10**	3-Point Hitch Cat 1	120 lbs	6", 9", 12"	✓	✓	✓	✓
<b>Rear Blades</b>	RB0548	3-Point Hitch Cat 1	128 lbs	48"	✓	✓	✓	✓
	RB0560		143 lbs	60"	✓	✓	✓	✓
	RB1560		248 lbs	60"	✓	✓	✓	✓
<b>Rotary Cutter</b>	RCR1242	3-Point Hitch Cat 1	383 lbs	42"	X	✓	✓	✓
	RCR1248		400 lbs	48"	X	✓	✓	✓
<b>Rotary Tillers</b>	RTA1242	3-Point Hitch Cat 1	391 lbs	42"	✓	✓	✓	✓
	RTA1250		421 lbs	50"	X	✓	✓	✓
	RTR0542		268 lbs	42"	✓	✓	✓	✓
	RTR0550		298 lbs	50"	✓	✓	✓	✓
	RTR1242		404 lbs	42"	✓	✓	✓	✓
	RTR1250		435 lbs	50"	X	✓	✓	✓
<b>Scarifiers</b>	SF2566	3-Point Hitch Cat 1	208 lbs	60"	X	X	✓	X
	SF2577		235 lbs	72"	X	X	✓	X
<b>Seedbed Rollers</b>	SBR72-3PT	3-Point Hitch Cat 1	486 lbs	69"	X	✓	✓	✓
	SBR72-PT	Drawbar Pull-Type	577 lbs	69"	✓	✓	✓	✓
<b>Snowblowers (Rear Mount)</b>	K51-20-06	3-Point Hitch Cat 1	1063 lbs	51" ext. to 56"	✓	✓	✓	✓
	K54-22-06		1088 lbs	54" ext. to 60"	X	✓	✓	✓
<b>Soil Pulverizer</b>	SP2060	3-Point Hitch Cat 1	491 lbs	60"	X	✓	✓	✓
<b>Spike-Tooth Harrow</b>	STH1590	Drawbar Pull-Type	237 lbs	90"	X	✓	✓	✓
<b>Spreaders</b>	FSP500**	3-Point Hitch Cat 1	119 lbs	37"	✓	✓	✓	✓
	FSP700**		128 lbs	44"	✓	✓	✓	✓
	PTS500**	Drawbar Pull-Type	165 lbs	41"	✓	✓	✓	✓
	PTS700**		176 lbs	41"	✓	✓	✓	✓
<b>Wood Chippers</b>	WC1503	3-Point Hitch Cat 1	369 lbs	3"	✓	✓	✓	✓
<b>Ballast / Weight Box</b>	WB10	3-Point Hitch Cat 1	Quick Hitch Compatible		✓	✓	✓	✓
	B5320		Not Quick Hitch Compatible		✓	✓	✓	✓
<b>Rear Quick Hitch</b>	QH05	3-Point Hitch Cat 1	37 lbs	n/a	✓	✓	✓	✓
	QH10		68 lbs	n/a	X	✓	✓	✓

## Performance Matched BX Series *Attachments*

TRACTOR ATTACHMENTS	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	BX1880	BX2380	BX2680	BX23S
Loader & Bucket BX80	LA344 <sup>1</sup>	Direct Pin Type	610 lbs	48"	✓	✓	✓	X
	LA344S <sup>1</sup>	2-Lever Quick Attach	650 lbs	48"	✓	✓	✓	X
Loader & Bucket BX23S	LA340 <sup>1</sup>	Direct Pin Type	610 lbs	48"	X	X	X	✓
	LA340S <sup>1</sup>	2-Lever Quick Attach	650 lbs	48"	X	X	X	✓
Backhoe & Buckets	BT603	4-Point Mount	607 lbs	8", 12", 16"	X	X	X	✓
Cab with Heat Option	BX4070	BX80 Cab	450 lbs	-	✓	✓	✓	X
	BX4090	BX23S Cab	450 lbs	-	X	X	X	✓
Angle Blade (Front Mount)	BX2812 <sup>2</sup>	4-Point Front Hitch	230 lbs	60"	✓	✓	✓	✓
V-Blade	BX2826 <sup>2</sup>	4-Point Front Hitch	280 lbs	52"	✓	✓	✓	✓
Broom (Front Mount)	BX2814 <sup>3</sup>	4-Point Front Hitch & K-Connect PTO	300 lbs	60"	✓	✓	✓	✓
Snowblowers (Front Mount)	BX2816 <sup>3</sup>	4-Point Front Hitch & K-Connect PTO	287 lbs	51"	✓	✓	✓	✓
	BX2830 <sup>3</sup>		305 lbs	48" HD	✓	✓	✓	✓
	BX2822 <sup>3</sup>		320 lbs	55" HD	✓	✓	✓	✓
4-Point Front Hitch	BX2810	Frame Mount	-	-	✓	✓	✓	✓
K-Connect PTO System	BX2811	Single Lever	-	-	✓	✓	✓	✓
Mid Mount Mowers (Standard)	RCK48-18BX	Shaft Driven PTO	165 lbs	48"	✓	X	X	X
	RCK54-23BX		210 lbs	54"	✓	✓	✓	✓
	RCK60B-23BX		250 lbs	60"	X	✓	✓	✓
Mid Mount Mowers (Drive-Over & Connect)	RCK54D-26BX-1	Shaft Driven PTO	227 lbs	54"	X	✓	✓	✓
	RCK60D-26BX-1		250 lbs	60"	X	✓	✓	✓
Grass Catcher	GCK60-26BX	Frame Mount	190 lbs	-	✓	✓	✓	✓

1- Requires Ballast

2- Requires 4-Point Front Hitch

3- Requires 4-Point Front Hitch + K-Connect



## Performance Matched BX Series Loader Attachments

LOADER ATTACHMENTS	MODEL	MOUNTING TYPE	WEIGHT (LBS)	WORKING WIDTH	BX1880	BX2380	BX2680	BX23S
Combo Buckets	CB0546 <sup>1</sup> (Fall 2021)	2-Lever Quick Attach	n/a	46"	✓	✓	✓	✓
	CB1050	Direct Pin Mount	266 lbs	50"	✓	✓	✓	✓
Grapples	SCG0548 <sup>1</sup>	Direct Pin Mount	156 lbs	48"	✓	✓	✓	✓
	SCG0554 <sup>1</sup>	2-Lever Quick Attach	180 lbs	54"	✓	✓	✓	✓
Pallet Forks (Loader Mount)	PFL1242 <sup>1</sup>	2-Lever Quick Attach	228 lbs	42"	✓	✓	✓	✓
Snow Pushers (Loader Mount)	SPL0548 <sup>1</sup>	Direct Pin Mount or	168 lbs	48"	✓	✓	✓	✓
	SPL0560 <sup>1</sup>	2-Lever Quick Attach	190 lbs	60"	✓	✓	✓	✓
Angle Blades (Loader Mount)	STB0554 <sup>1</sup>	2-Lever Quick Attach	278 lbs	54"	✓	✓	✓	✓
	STB0560 <sup>1</sup>		288 lbs	60"	✓	✓	✓	✓

1- Requires Ballast

### Notice:

The above identified implements are either manufactured by Kubota or have received an Engineering Release approving use by Kubota, and thus meet the performance matching requirements for the specified power machines for normally anticipated operating conditions. The specifications above are intended for general application; unusual soil, terrain, or severe operating conditions may not allow for the use of a specific implement under those operating conditions. The use of implements or attachments which are neither manufactured or approved by Kubota for use with the specified power machines and which do not meet the above specifications may result in malfunctions or damage to the power machine, damage to other property and/or injury to the operator or to others. Any such malfunctions or damages are not covered by the Kubota express limited warranty. The power machine, implement, and operating conditions need to be evaluated and monitored by the operator to be sure that the conditions are within a safe operating envelope for general use.

- Check with the tractor manual to verify for proper ballasting when using an implement or attachment on the machine.
- Additional kits (Rear Remotes, Third Function valves, etc.) may be required in order to use any of the above implements. Check with your local dealer to determine what is needed for proper fitment and operation.
- (\*\*) This implement/attachment is approved for the base weight, but allows for additional ballasting (concrete blocks, seed, water tanks). Verify with the tractor manual and ensure proper ballasting before adding any additional weight to the implement/attachment.

Kubota Canada Ltd. notes that specifications and technical information are subject to changes without notice and Kubota does not represent or warrant that the information in this publication is completely accurate or current; however, Kubota used reasonable efforts to set forth and include accurate and up to date information in this publication. Kubota disclaims all representations and warranties, whether express or implied, including, but not limited to, warranties of merchantability and fitness for a particular purpose and Kubota shall not be liable for any damages, whether compensatory, direct, indirect, incidental, special, or consequential, arising out of or in connection with the use of this publication, or in the information therein.

