

The Best Time to Replace Skylights

Is when a professional is on the roof!



The No Leak Skylight™

Old, outdated skylights can't hold a candle to the VELUX No Leak Skylight! That's why when you're replacing a roof, it's also the perfect time to upgrade the existing skylights to VELUX No Leak Skylights. Not only do VELUX No Leak Skylights offer 3 layers of protection against leaks, but they're also available in solar-powered models and with factory-installed blinds.

Measuring Skylights for Replacements

1. On the roof, measure where the shingles meet the existing skylight flashing, width first then length.
 - a. The outside curb or frame measurement will be approx. 1" larger than shown on size chart due to flashing and roofing material.
2. Inside, measure drywall at the highest point where it touches the skylight.
 - a. Add approximately 2" – 3" for deck-mounted skylights
 - b. Add approximately 4" for curb-mounted skylights

Remember: Pictures with tape measurements are the best way to ensure accurate sizing for skylight replacement. The standard size charts are a guide, VELUX does not guarantee an exact fit.

Deck-Mounted Skylight Model Sizes

		A06	C01	C04	C06	C08	C12	D26	D06	M02	M04	M06	M08	S01	S06
Outside Frame	(W-in. x H-in.)	15 1/4 x 46 1/4	21 1/2 x 27 3/8	21 1/2 x 38 3/8	21 1/2 x 46 1/4	21 1/2 x 54 15/16	21 1/2 x 70 3/4	23 1/4 x 23 3/16	23 1/4 x 46 1/4	30 9/16 x 30 1/2	30 9/16 x 38 3/8	30 9/16 x 46 1/4	30 9/16 x 54 15/16	44 3/4 x 27 3/8	44 3/4 x 46 1/4

Model FS sizes D26 and D06 fit perfectly between roof trusses.

Curb-Mounted Skylight Model Sizes

		1430	1446	2222	2230	2234	2246	2270	3030	3046	3055	3434	3446	4622	4646
Outside Curb	(W-in. x H-in.)	17 1/2 x 33 1/2	17 1/2 x 49 1/2	25 1/2 x 25 1/2	25 1/2 x 33 1/2	25 1/2 x 37 1/2	25 1/2 x 49 1/2	25 1/2 x 73 1/2	33 1/2 x 33 1/2	33 1/2 x 49 1/2	33 1/2 x 58 1/2	37 1/2 x 37 1/2	37 1/2 x 49 1/2	49 1/2 x 25 1/2	49 1/2 x 49 1/2

The No Leak Promise - 3 Layers of Protection

- 1 Pre-Attached Seal**
Pre-attached deck seal (deck-mounted) or gasket (curb-mounted) provides a tight seal for leak-proof installation.
- 2 Adhesive Underlayment**
Adhesive underlayment for secondary water protection against the harshest weather conditions.
- 3 Engineered Flashing**
Engineered flashing for easy installation and primary water protection.*



*To qualify for the VELUX 10-year installation warranty, VELUX flashing must be purchased. The 10-year installation warranty excludes EVMS, EV, QPF, EF.



The No Leak Skylight™



Eligible for
**Federal Solar
Tax Credit***
on product and
installation

Go Solar with VELUX!

Save Your Customers Money

When you add solar-powered products to your project, your customers will be eligible for a federal solar tax credit on their entire purchase and installation.

Solar Powered
"Fresh Air" Skylight



Manual "Fresh Air" Skylight or Fixed Skylight
with a pre-installed solar blind



Sun Tunnel® Skylight
with a Solar Night Light



*Based on tax credit eligibility. For more information visit veluxusa.com/go-solar. V-4740-0120